

Product line

Excavators

Mini



Crawler



Wheel



Model	Engine	Horse power rated (kW/hp)	Operating weight (kg/lb)	Bucket capacity (SAE, m ³ /yd ³)
HX10A	YM 3TNV70 (S5)	9.7 / 13	1650 / 3640	0.04 / 0.05
R16-9	MT L3E (T4)	12.5 / 16.8	1650 / 3640	0.04 / 0.05
R17Z-9A	KB D902 (T4F)	12.5 / 16.8	1700 / 3750	0.04 / 0.05
R18-9	MT L3E (T4F)	14.0 / 18.8	1855 / 4089	0.04 / 0.05
R18-9AK	KB D902 (S5)	12.1 / 16.2	1855 / 4089	0.04 / 0.05
R25Z-9A	MT S3L2 (T4I)	18.4 / 24.7	2600 / 5730	0.07 / 0.09
R25Z-9AK	KB D1305 (T4F)	18.5 / 24.8	2580 / 5690	0.07 / 0.09
R27Z-9	MT S3L2 (TFI)	18.4 / 24.7	2880 / 6350	0.08 / 0.10
R30Z-9AK	KB D1305 (T4F)	18.5 / 24.8	3005 / 6620	0.08 / 0.10
R35Z-7	YM 3TNV88 (T2)	20 / 27	3650 / 8050	0.11 / 0.14
R35Z-7A	YM 3TNV88 (T3)	20.4 / 27.3	3650 / 8050	0.11 / 0.14
R35Z-9	YM 3TNV88 (T3)	20.4 / 27.3	3650 / 8050	0.11 / 0.14
R35Z-9A	YM 3TNV88F (T4F)	18.2 / 24.4	3690 / 8140	0.11 / 0.14
R55-7	YM 4TNV94L (T2)	40 / 53	5700 / 12570	0.07 ~ 0.18 / 0.09 ~ 0.24
R55-7A	YM 4TNV98 (T3)	42.5 / 57	5700 / 12570	0.07 ~ 0.18 / 0.09 ~ 0.24
R55-9	YM 4TNV98 (T4I)	42.5 / 57.0	5650 / 12460	0.07 ~ 0.18 / 0.09 ~ 0.24
R55-9A	YM 4TNV98C (T4F)	49.9 / 66.9	5650 / 12460	0.07 ~ 0.18 / 0.09 ~ 0.24
R60-9S	YM 4TNV94L (T2)	39 / 52.3	5650 / 12460	0.07 ~ 0.18 / 0.09 ~ 0.24
R60CR-9	YM 4TNV98 (T4I)	42.5 / 57.8	5900 / 13010	0.07 ~ 0.18 / 0.09 ~ 0.24
R60CR-9A	YM 4TNV98C (T4F)	48.3 / 64.7	5900 / 13010	0.07 ~ 0.18 / 0.09 ~ 0.24
HX60S	YM 4TNV94L (T4F)	36.2 / 48.5	5720 / 12610	0.21 / 0.28
R80-7	YM 4TNV98 (T2)	43 / 58	7800 / 17200	0.28 ~ 0.31 / 0.37 ~ 0.41
R80-7A	YM 4TNV98 (T3)	44.4 / 59.6	7800 / 17200	0.28 ~ 0.31 / 0.37 ~ 0.41
R80CR-9	YM 4TNV98 (T4I)	44.4 / 59.5	8350 / 18410	0.14 ~ 0.28 / 0.18~0.37
R80CR-9A	YM 4TNV98C (T4F)	49.9 / 66.9	8350 / 18410	0.28 / 0.37
HX85A	YM 4TNV98C (S5)	49.9 / 66.9	8530 / 18810	0.25 / 0.33
R110-7	MT S4K-T (T2)	70 / 94	11200 / 24690	0.30 ~ 0.59 / 0.39 ~ 0.77
R110-7A	MT D04FD (T3)	72 / 97	11200 / 24690	0.30 ~ 0.59 / 0.39 ~ 0.77
R125LCR-9A	PK 1204E (T4F)	74.3 / 100	12500 / 27560	0.40 ~ 0.45 / 0.52 ~ 0.59
HX130 LCR	PK 854F (T4F)	55 / 73.6	12700 / 28600	0.30 ~ 0.59 / 0.39 ~ 0.77
R140LC-7	CM B3.9 (T2)	80 / 107	13980 / 30860	0.23 ~ 0.71 / 0.30 ~ 0.93
R140LC-7A	MT D04FD (T3)	89 / 119	13980 / 30820	0.23 ~ 0.71 / 0.30 ~ 0.93
R140LC-9	MT D04FD (T3)	78 / 105	13980 / 30820	0.23 ~ 0.71 / 0.30 ~ 0.93
R140LC-9A	PK 1204E (T4F)	92.7 / 124	14600 / 32190	0.23 ~ 0.71 / 0.30 ~ 0.93

※ Engine

CM : Cummins

MT : Mitsubishi

YM : Yanmar

PK : Perkins

KB : Kubota

Product line

Excavators

Mini



Crawler



Wheel



Model	Engine	Horse power rated (kW/hp)	Operating weight (kg/lb)	Bucket capacity (SAE, m ³ /yd ³)
R140LC-9S	CM B3.9 (T2)	78 / 105	13980 / 30820	0.23 ~ 0.71 / 0.30 ~ 0.93
R145CR-9	MT D04FD (T3)	78 / 105	14600 / 32190	0.23 ~ 0.71 / 0.30 ~ 0.93
R145CR-9A	PK 1204E (T4F)	87 / 116	14600 / 32190	0.23 ~ 0.71 / 0.30 ~ 0.93
HX140 L	PK 1204F (T4F)	92.6 / 124	14200 / 31310	0.23 ~ 0.71 / 0.30 ~ 0.93
HX140 LC	CM QSF3.8 (T4F)	95 / 127	14050 / 30975	0.23 ~ 0.71 / 0.30 ~ 0.93
HX145 LCR	PK 1204F (T4F)	92.6 / 124	14780 / 32580	0.23 ~ 0.71 / 0.30 ~ 0.93
HX145LCRT3	CM QSB4.5 (T3)	97 / 130	14880 / 32800	0.52 ~ 0.71 / 0.68 ~ 0.93
R160LC-7	MT S6S-DT (T2)	94 / 126	17400 / 38360	0.39 ~ 0.89 / 0.51 ~ 1.16
R160LC-7A	MT D04FD (T3)	94 / 126	17400 / 38360	0.39 ~ 0.89 / 0.51 ~ 1.16
R160LC-9	MT D04FD (T3)	87 / 116	17800 / 39240	0.39 ~ 0.89 / 0.51 ~ 1.16
R160LC-9A	PK 1204E (T4F)	96 / 128	17800 / 39240	0.39 ~ 0.89 / 0.51 ~ 1.16
R160LC-9S	MT S6S-DT (T2)	87 / 116	17800 / 39240	0.39 ~ 1.05 / 0.51 ~ 1.37
HX160 L	PK 1204F (T4F)	102 / 137	18100 / 39900	0.39 ~ 1.05 / 0.51 ~ 1.37
R180LC-7	MT S6S-DT (T2)	94 / 126	18200 / 40120	0.39 ~ 1.05 / 0.51 ~ 1.37
R180LC-7A	MT D04FD (T3)	94 / 126	18200 / 40120	0.39 ~ 1.05 / 0.51 ~ 1.37
R180LC-9	MT D04FD (T3)	87 / 116	18600 / 41010	0.39 ~ 1.05 / 0.51 ~ 1.37
R180LC-9A	PK 1204E (T4F)	96 / 128	18600 / 41010	0.39 ~ 1.05 / 0.51 ~ 1.37
R180LC-9S	MT S6S-DT (T2)	87 / 116	18600 / 41010	0.39 ~ 1.05 / 0.51 ~ 1.37
HX180 L	PK 1204F (T4F)	102 / 137	18800 / 41450	0.39 ~ 1.05 / 0.51 ~ 1.37
R210LC-7	HD HM5.9 (T2)	116 / 155	21700 / 47840	0.51 ~ 1.34 / 0.67 ~ 1.75
R210LC-7(#98001-)	CM 6BTAA (T2)	112 / 150	21700 / 47840	0.52 ~ 1.20 / 0.67 ~ 1.57
R210LC-7A	CM QSB6.7 (T3)	113 / 151	21700 / 47840	0.51 ~ 1.34 / 0.67 ~ 1.75
R210LC-7H	HD D6BV (T2)	107 / 143	21500 / 47400	0.51 ~ 1.34 / 0.67 ~ 1.75
R210LC-7H(#9001-)	HD D6BT (T2)	103 / 137	21500 / 47400	0.52 ~ 1.20 / 0.67 ~ 1.57
R210LC-9	HD HE6.7 (T3)	113 / 151	21900 / 48280	0.51 ~ 1.34 / 0.67 ~ 1.75
R210NLC-7	CM 6BTAA (T2)	112 / 150	21500 / 47400	0.51 ~ 1.34 / 0.67 ~ 1.75
R210NLC-7A	CM QSB6.7 (T3)	113 / 151	22000 / 48500	0.51 ~ 1.34 / 0.67 ~ 1.75
R210NLC-9	HD HE6.7 (T3)	113 / 151	22000 / 48500	0.51 ~ 1.34 / 0.67 ~ 1.75
HX210A L	CM B4.5 (S5)	129 / 173	22150 / 48830	0.80 ~ 1.34 / 1.05 ~ 1.75
HX210A NL	CM B4.5 (S5)	129 / 173	22800 / 50270	0.80 ~ 1.34 / 1.05 ~ 1.75
HX210S	*HD HM3.9	110 / 148	20830 / 45920	0.90 ~ 1.20 / 1.18 ~ 1.57
R220LC-7H	HD D6BV (T2)	117 / 159	21500 / 47400	0.51 ~ 1.34 / 0.67 ~ 1.75
R220LC-9A	CM QSB6.7 (T4F)	124 / 167	21900 / 48280	0.51 ~ 1.34 / 0.67 ~ 1.75

※ Engine

CM : Cummins HD : Hyundai MT : Mitsubishi PK : Perki s

* : Non tier (BS II)

Product line

Excavators

Mini



Crawler



Wheel



Model	Engine	Horse power rated (kW/hp)	Operating weight (kg/lb)	Bucket capacity (SAE, m ³ /yd ³)
R220LC-9S	HD HM5.9 (T2)	112 / 150	21900 / 48280	0.51 ~ 1.34 / 0.67 ~ 1.75
R220LC-9SH	HD D6BV (T2)	107 / 145	21900 / 48280	0.51 ~ 1.34 / 0.67 ~ 1.75
R220NLC-9A	CM QSB6.7 (T4F)	118 / 158	22000 / 48500	0.51 ~ 1.34 / 0.67 ~ 1.75
HX220 L	CM QSB6.7 (T4F)	136 / 183	22100 / 48720	0.52 ~ 1.34 / 0.68 ~ 1.75
HX220 NL	CM QSB6.7 (T4F)	136 / 183	22300 / 49160	0.80 ~ 1.34 / 1.05 ~ 1.75
HX220A L	CM B6.7 (S5)	129 / 173	22280 / 49120	0.80 ~ 1.34 / 1.05 ~ 1.75
HX220S	*HD HM3.9	110 / 148	21260 / 45920	0.90 ~ 1.20 / 1.18 ~ 1.57
HX220LT3	HD HE6.7 (T3)	119 / 160	21970 / 48440	0.52 ~ 1.34 / 0.68 ~ 1.75
HX225S L	CM B5.9 (T2)	110 / 147	22070 / 48660	0.52 ~ 1.34 / 0.68 ~ 1.75
R235LCR-9	HD HE6.7 (T3)	113 / 151	23800 / 52470	0.51 ~ 1.34 / 0.67 ~ 1.75
R235LCR-9A	CM QSB6.7 (T4F)	124 / 167	23800 / 52470	0.51 ~ 1.34 / 0.67 ~ 1.75
HX235 LCR	CM QSB6.7 (T4F)	136 / 183	24000 / 52910	0.80 / 1.05
HX235A LCR	CM B6.7 (S5)	129 / 173	24480 / 53970	0.80 ~ 1.34 / 1.05 ~ 1.75
HX235LCRT3	HD HE6.7 (T3)	119 / 160	24200 / 53350	0.80 ~ 1.34 / 1.05 ~ 1.75
R250LC-7	CM B5.9 (T2)	133 / 178	25200 / 55600	0.60 ~ 1.50 / 0.78 ~ 1.96
R250LC-7A	CM QSB6.7 (T3)	131 / 176	25200 / 55600	0.60 ~ 1.50 / 0.78 ~ 1.96
R250LC-9	HD HE6.7 (T3)	146 / 195	25200 / 55600	0.60 ~ 1.50 / 0.78 ~ 1.96
R260LC-9A	CM QSB6.7 (T4F)	140 / 188	25200 / 55600	0.60 ~ 1.50 / 0.78 ~ 1.96
R260LC-9S	HD HM5.9 (T2)	133 / 178	25200 / 55600	0.60 ~ 1.50 / 0.78 ~ 1.96
HX260 L	CM QSB6.7 (T4F)	142 / 190	25600 / 56440	1.08 ~ 1.50 / 1.41 ~ 1.96
HX260A L	CM B6.7 (S5)	173 / 232	27000 / 59520	1.08 ~ 1.50 / 1.41 ~ 1.96
HX260LT3	CM HE6.7 (T3)	142 / 190	26060 / 57450	1.08 ~ 1.50 / 1.41 ~ 1.96
R290LC-7	CM QSB (T2)	159 / 213	29300 / 64600	0.79 ~ 1.85 / 1.03 ~ 2.42
R290LC-7H	HD D6AZ (T2)	149 / 200	28800 / 63500	0.79 ~ 1.85 / 1.03 ~ 2.42
R290LC-7A	CM QSB6.7 (T3)	169 / 227	29300 / 64600	0.79 ~ 1.85 / 1.03 ~ 2.42
R290LC-9	HD HE6.7 (T3)	169 / 227	29300 / 64600	0.79 ~ 1.85 / 1.03 ~ 2.42
R290LC-9 MH	CM QSB6.7 (T3)	169 / 227	32710 / 72110	**10.90 / 1.18
R300LC-7	HD D6AC (T2)	162 / 217	29600 / 65300	0.79 ~ 1.85 / 1.03 ~ 2.42
R300LC-9A	CM QSB6.7 (T4F)	168 / 225	29800 / 65700	0.79 ~ 1.85 / 1.03 ~ 2.42
R300LC-9S	HD HM8.3 (T2)	196 / 263	29700 / 65480	0.79 ~ 1.85 / 1.03 ~ 2.42
R300LC-9SH	HD D6AC (T2)	162 / 217	29900 / 65920	0.79 ~ 1.85 / 1.03 ~ 2.42
HX300 L	CM QSB6.7 (T4F)	180 / 242	30200 / 66580	0.52 ~ 1.85 / 0.68 ~ 2.42
HX300A L	CM B6.7 (S5)	194 / 260	30980 / 68300	0.52 ~ 1.85 / 0.68 ~ 2.42

※ Engine

CM : Cummins HD : Hyundai

* : Non tier (BS II) ** : Grapple

Product line

Excavators

Mini



Crawler



Wheel



Model	Engine	Horse power rated (kW/hp)	Operating weight (kg/lb)	Bucket capacity (SAE, m ³ /yd ³)
HX300S L	HD HM8.3 (T2)	187 / 250	30200 / 66580	0.52 ~ 1.85 / 0.68 ~ 2.42
HX300LT3	HD HE6.7 (T3)	164 / 220	29980 / 66090	0.52 ~ 1.85 / 0.68 ~ 2.42
R305LC-7	CM C8.3 (T2)	190 / 255	29300 / 64600	0.79 ~ 1.85 / 1.03 ~ 2.42
R320LC-7	CM C8.3 (T2)	193 / 259	32200 / 70990	0.90 ~ 2.10 / 1.18 ~ 2.75
R320LC-7A	CM QSC (T3)	193 / 258	32200 / 71000	0.90 ~ 2.10 / 1.18 ~ 2.75
R320LC-9	CM QSC (T3)	196 / 263	32200 / 71000	0.90 ~ 2.10 / 1.18 ~ 2.75
R330LC-9A	CM QSL9 (T4F)	210 / 282	33000 / 72750	0.90 ~ 2.10 / 1.18 ~ 2.75
R330LC-9S	HD HM8.3 (T2)	193 / 259	32700 / 72090	0.90 ~ 2.10 / 1.18 ~ 2.75
R330LC-9SH	HD D6A (T2)	206 / 276	33000 / 72750	0.90 ~ 2.10 / 1.18 ~ 2.75
HX330 L	CM QSL9 (T4F)	212 / 284	33500 / 73850	0.90 ~ 2.10 / 1.18 ~ 2.75
HX330A L, HX350A L	CM L9 (S5)	231 / 310	33680 / 74096	1.44 ~ 2.10 / 1.88 ~ 2.75
HX330S L	HD HM8.3 (T2)	187 / 250	33000 / 72750	0.90 ~ 2.10 / 1.18 ~ 2.75
HX340S L	HD HM8.3 (T2)	194 / 260	33000 / 72750	1.44 ~ 2.10 / 1.88 ~ 2.75
HX350LT3	CM QSC (T3)	209 / 280	33680 / 74096	1.44 ~ 2.10 / 1.88 ~ 2.75
R360LC-7	CM QSC8.3 (T2)	209 / 280	36100 / 79590	1.15 ~ 2.32 / 1.50 ~ 3.03
R360LC-7A	CM QSL (T3)	221 / 296	36100 / 79590	1.15 ~ 2.32 / 1.50 ~ 3.03
R370LC-7	HD D6AC (T2)	206 / 276	36900 / 81350	1.15 ~ 2.32 / 1.50 ~ 3.03
R380LC-9	HD HE8.9 (T3)	202 / 271	38200 / 84220	1.15 ~ 2.32 / 1.50 ~ 3.03
R380LC-9 DM	HD HE8.9 (T3)	221 / 296	45420 / 100130	-
R380LC-9 MH	CM QSL (T3)	221 / 296	43240 / 95330	**11.20 / 1.57
R380LC-9A	CM QSL9 (T4F)	231 / 310	38200 / 84220	1.46 ~ 2.32 / 1.91 ~ 3.03
R380LC-9SH	HD D6AC (T2)	206 / 276	38400 / 84660	1.46 ~ 2.32 / 1.91 ~ 3.03
HX380 L	CM QSL9 (T4F)	236 / 316	38920 / 85800	1.46 ~ 2.32 / 1.91 ~ 3.03
HX380A L	CM L9 (S5)	272 / 365	40000 / 88000	1.46 ~ 2.32 / 1.91 ~ 3.03
R430LC-9	HD HE8.9 (T3)	221 / 296	42600 / 93920	1.90 ~ 2.10 / 2.49 ~ 2.75
R430LC-9A	CM QSL9 (T4F)	231 / 310	42600 / 93920	1.90 ~ 2.10 / 2.49 ~ 2.75
R430LC-9SH	HD D6AC (T2)	206 / 276	42600 / 93920	1.90 ~ 2.10 / 2.49 ~ 2.75
HX430 L	CM QSL9 (T4F)	267 / 358	44120 / 97270	1.90 ~ 2.10 / 2.49 ~ 2.75
R450LC-7	CM QSM11 (T2)	239 / 320	44900 / 99000	1.38 ~ 3.03 / 1.80 ~ 3.96
R450LC-7A	CM QSM11 (T3)	266 / 357	45200 / 99650	1.38 ~ 3.03 / 1.80 ~ 3.96
R480LC-9	CM QSM11 (T3)	266 / 357	48100 / 106040	1.00 ~ 3.03 / 1.30 ~ 3.96
R480LC-9 MH	CM QSM11 (T3)	266 / 357	55210 / 121720	**11.40 / 1.83
R480LC-9A	CM QSM11.9 (T4F)	277 / 372	48100 / 106040	1.00 ~ 3.03 / 1.30 ~ 3.96

※ Engine

CM : Cummins HD : Hyundai

** : Grapple

Product line

Excavators

Mini



Crawler



Wheel



Model	Engine	Horse power rated (kW/hp)	Operating weight (kg/lb)	Bucket capacity (SAE, m ³ /yd ³)
R480LC-9S	CM QSM11 (T2)	266 / 357	48100 / 106040	1.00 ~ 3.03 / 1.30 ~ 3.96
HX480 L	SC DC13 (T4F)	331 / 444	49500 / 109130	1.00 ~ 3.20 / 1.30 ~ 4.19
HX480S L	CM QSM11 (T2)	263 / 353	49515 / 109160	1.38 ~ 3.20 / 1.80 ~ 4.19
R500LC-7	CM QSM11 (T2)	263 / 353	48800 / 107580	1.38 ~ 3.60 / 1.80 ~ 4.71
R500LC-7A	CM QSM11 (T3)	266 / 357	48800 / 107580	1.38 ~ 3.60 / 1.80 ~ 4.71
R520LC-9	CM QSM11 (T3)	266 / 357	51000 / 112430	1.00 ~ 3.20 / 1.30 ~ 4.19
R520LC-9 DM	CM QSM11 (T3)	266 / 357	58700 / 129410	-
R520LC-9A	CM QSX11.9 (T4F)	277 / 372	51000 / 112430	1.00 ~ 3.03 / 1.30 ~ 3.96
R520LC-9S	CM QSM11 (T2)	266 / 357	51000 / 112430	1.00 ~ 3.03 / 1.30 ~ 3.96
HX520 L	SC DC13 (T4F)	331 / 444	52400 / 115520	1.00 ~ 3.20 / 1.30 ~ 4.19
HX520S L	CM QSM11 (T2)	263 / 353	51175 / 112820	1.38 ~ 3.20 / 1.80 ~ 4.19
R700LC-9	SC DC16 074A (T2)	405 / 550	72400 / 156610	3.30 ~ 4.60 / 4.32 ~ 6.02
R800LC-7A	CM QSX15 (T3)	380 / 510	82320 / 181480	3.40 ~ 5.10 / 4.45 ~ 6.67
R800LC-7A FS	CM QSX15 (T3)	366 / 490	86700 / 191140	4.50 ~ 5.10 / 5.89 ~ 6.60
R800LC-9	CM QSX15 (T3)	380 / 510	83400 / 183860	2.56 ~ 5.10 / 3.35 ~ 6.67
R800LC-9 FS	CM QSX15 (T3)	366 / 490	87800 / 193560	4.50 / 5.89
R850LC-9	CM QSX15 (T3)	380 / 510	83120 / 183250	1.65~4.50 / 2.16~5.88
R850LC-9 FS	CM QSX15 (T3)	366 / 490	87800 / 193560	4.50 / 5.89
HX900 L	SC DC16 (T4F)	478 / 641	88800 / 195770	3.60~5.40 / 4.71~7.06
R1200-9	CM QSK23 (T2)	567 / 760	118000 / 260140	6.70 / 8.76
R1250-9	CM QSK23 (T2)	567 / 760	118000 / 260140	6.70 / 8.76
R55W-7	YM 4TNV94L (T2)	42 / 57	5600 / 12350	0.07 ~ 0.18 / 0.09 ~ 0.24
R55W-7A	YM 4TNV98 (T3)	42.5 / 57	5600 / 12350	0.07 ~ 0.18 / 0.09 ~ 0.24
R55W-9	YM 4TNV98 (T3)	42.5 / 57	5550 / 12240	0.07 ~ 0.18 / 0.09 ~ 0.24
R55W-9A	YM 4TNV98C (T4I)	49.9 / 66.9	5550 / 12240	0.07 ~ 0.18 / 0.09 ~ 0.24
R60W-9S	YM 4TNV94L (T2)	41.2 / 55.3	5550 / 12240	0.07 ~ 0.18 / 0.09 ~ 0.24
R140W-7	CM B3.9 (T2)	86 / 115	13500 / 29760	0.23 ~ 0.71 / 0.30 ~ 0.93
R140W-7A	MT D04FD (T3)	89 / 119	13500 / 29760	0.23 ~ 0.71 / 0.30 ~ 0.93
R140W-9	HD HM6.7 (T3)	99 / 133	13700 / 30200	0.23 ~ 0.71 / 0.30 ~ 0.93
R140W-9A	CM QSB 6.7 (T4I)	109 / 146	13700 / 30200	0.23 ~ 0.71 / 0.30 ~ 0.93
R140W-9S	CM B3.9 (T1)	78 / 105	13700 / 30200	0.23 ~ 0.71 / 0.30 ~ 0.93
HW140	CM QSB 6.7 (T4F)	117 / 157	13880 / 30600	0.23 ~ 0.71 / 0.30 ~ 0.93
R160W-9A	CM QSB 6.7 (T4I)	123 / 165	16700 / 36820	0.39 ~ 0.89 / 0.51 ~ 1.16
HW160	CM QSB 6.7 (T4F)	134 / 180	17100 / 37700	0.39 ~ 1.05 / 1.51 ~ 1.37

※ Engine

CM : Cummins

HD : Hyundai

MT : Mitsubishi

YM : Yanmar

SC : Scania

Product line

Excavators

Mini



Crawler



Wheel



Model	Engine	Horse power rated (kW/hp)	Operating weight (kg/lb)	Bucket capacity (SAE, m ³ /yd ³)
R170W-7	MT S6S-DT (T2)	94 / 126	16200 / 35710	0.39 ~ 1.05 / 1.51 ~ 1.37
R170W-7A	MT D04FD (T3)	94 / 126	16400 / 36160	0.39 ~ 1.05 / 1.51 ~ 1.37
R170W-9	HD HM6.7 (T3)	114 / 153	17300 / 38140	0.39 ~ 1.05 / 1.51 ~ 1.37
R170W-9S	MT S6S-DT (T2)	94 / 128	17300 / 38140	0.39 ~ 1.05 / 1.51 ~ 1.37
R180W-9A	CM QSB 6.7 (T4I)	123 / 165	17280 / 38100	0.39 ~ 1.05 / 1.51 ~ 1.37
R180W-9S	MT S6S-DT (T2)	94 / 126	18420 / 40610	0.39 ~ 1.05 / 1.51 ~ 1.37
HW180	CM QSB6.7 (T4F)	134 / 180	17800 / 39240	0.39 ~ 1.05 / 1.51 ~ 1.37
R200W-7	CM B5.9 (T2)	124 / 166	20500 / 45200	0.51 ~ 1.34 / 0.67 ~ 1.75
R200W-7A	CM QSB 6.7 (T3)	122 / 164	20500 / 45200	0.51 ~ 1.34 / 0.67 ~ 1.75
R210W-9	HD HM6.7 (T3)	125 / 168	20500 / 45200	0.51 ~ 1.34 / 0.67 ~ 1.75
R210W-9 MH	HD HM6.7 (T3)	131 / 176	25700 / 56660	**10.70 / 0.92
R210W-9A	CM QSB 6.7 (T4I)	129 / 173	20500 / 45200	0.51 ~ 1.34 / 0.67 ~ 1.75
R210W-9A MH	HD HM6.7 (T4I)	129 / 173	25700 / 56660	**10.70 / 0.92
R210W-9S	HD HM5.9 (T2)	124 / 166	20500 / 45200	0.51 ~ 1.34 / 0.67 ~ 1.75
HW210	CM QSB 6.7 (T4F)	137 / 183	21200 / 46740	0.80 ~ 1.34 / 1.05 ~ 1.75

※ Engine

CM : Cummins

HD : Hyundai

MT : Mitsubishi

** : Grapple

Product line

Wheel loaders



Model	Engine	Horse power rated (kW/hp)	Operating weight (kg/lb)	Bucket capacity (SAE, m ³ /yd ³)
HL730-7	CM B3.9 (T2)	93 / 125	9700 / 21380	1.60 ~ 2.10 / 2.10 ~ 2.70
HL730TM-7	CM B3.9 (T2)	93 / 125	10000 / 22050	1.40 ~ 1.90 / 1.80 ~ 2.50
HL730-7A	CM QSB4.5 (T3)	93 / 125	9700 / 21400	1.60 ~ 2.10 / 2.10 ~ 2.70
HL730TM-7A	CM QSB4.5 (T3)	93 / 125	10000 / 22050	1.40 ~ 1.90 / 1.80 ~ 2.50
HL730-9	CM QSB4.5 (T3)	93 / 125	9800 / 21600	1.70 ~ 2.40 / 2.22 ~ 3.14
HL730TM-9	CM QSB4.5 (T3)	93 / 125	10200 / 22490	1.40 ~ 1.90 / 1.80 ~ 2.50
HL730-9A	CM QSB4.5 (T4I)	97 / 130	10500 / 23150	1.70 ~ 2.40 / 2.22 ~ 3.14
HL730TM-9A	CM QSB4.5 (T4I)	97 / 130	10900 / 24030	1.40 ~ 1.90 / 1.80 ~ 2.50
HL730-9S	CM QSB4.5 (T2)	93 / 125	9700 / 21400	1.70 ~ 2.40 / 2.22 ~ 3.14
HL930A	CM B4.5 (S5)	99 / 133	11500 / 25355	1.80 ~ 1.90 / 2.40 ~ 2.50
HL930A TM	CM B4.5 (S5)	99 / 133	11960 / 26370	1.70 ~ 1.90 / 2.22 ~ 2.50
HL935	CM QSB6.7 (T4F)	118 / 158	12700 / 29000	1.90 ~ 2.40 / 2.50 ~ 3.14
HL740-7	CM QSB5.9 (T2)	104 / 140	11500 / 25350	1.70 ~ 2.30 / 2.20 ~ 3.00
HL740TM-7	CM QSB5.9 (T2)	104 / 140	12050 / 26570	1.70 ~ 2.00 / 2.20 ~ 2.60
HL740-7A	CM QSB6.7 (T3)	108 / 145	11550 / 25460	1.70 ~ 2.30 / 2.20 ~ 3.00
HL740TM-7A	CM QSB6.7 (T3)	108 / 145	12100 / 26700	1.70 ~ 2.00 / 2.20 ~ 2.60
HL740-7S	CM 6BTA5.9 (T2)	112 / 150	*10500 / 23100 10730 / 23650	1.70 ~ 2.30 / 2.20 ~ 3.00
HL740-9	HD HM6.7 (T3)	108 / 145	12000 / 26460	2.00 ~ 2.80 / 2.60 ~ 3.70
HL740TM-9	HD HM6.7 (T3)	108 / 145	12600 / 27780	2.00 ~ 2.50 / 2.60 ~ 3.30
HL740-9A	CM QSB6.7 (T4I)	117 / 158	12700 / 29000	2.00 ~ 2.80 / 2.60 ~ 3.70
HL740TM-9A	CM QSB6.7 (T4I)	117 / 158	13300 / 29320	2.00 ~ 2.50 / 2.60 ~ 3.30
HL740-9S	CM 6BTA5.9 (T2)	112 / 150	11550 / 25460	2.00 ~ 2.80 / 2.60 ~ 3.70
HL940	CM QSB6.7 (T4F)	118 / 158	13100 / 28880	2.10 ~ 2.70 / 2.70 ~ 3.50
HL940 TM	CM QSB6.7 (T4F)	118 / 158	13600 / 29980	2.10 ~ 2.30 / 2.70 ~ 3.00
HL940A	CM B6.7 (S5)	116 / 156	13400 / 29540	2.10 ~ 2.30 / 2.70 ~ 3.00
HL940A TM	CM B6.7 (S5)	116 / 156	13800 / 30420	2.30 / 3.00
HL757-7	CM QSB5.9 (T2)	129 / 173	13800 / 30420	2.30 ~ 3.20 / 3.00 ~ 4.20
HL757TM-7	CM QSB5.9 (T2)	129 / 173	14300 / 31530	2.30 ~ 2.70 / 3.00 ~ 3.50
HL757-7A	CM QSB6.7 (T3)	129 / 173	14500 / 31970	2.30 ~ 3.20 / 3.00 ~ 4.20
HL757TM-7A	CM QSB6.7 (T3)	129 / 173	15000 / 33070	2.30 ~ 2.70 / 3.00 ~ 3.50
HL757-7S	CM 6BTA5.9 (T2)	123 / 165	*13000 / 28600 13180 / 29100"	2.30 ~ 3.20 / 3.00 ~ 4.20
HL757-9	HD HM6.7 (T3)	129 / 173	14500 / 31970	2.30 ~ 3.20 / 3.00 ~ 4.20
HL757TM-9	HD HM6.7 (T3)	129 / 173	15000 / 33070	2.30 ~ 2.70 / 3.00 ~ 3.50

※ Engine

CM : Cummins HD : Hyundai

* : Canopy

Product line

Wheel loaders



Model	Engine	Horse power rated (kW/hp)	Operating weight (kg/lb)	Bucket capacity (SAE, m ³ /yd ³)
HL757TM-9	HD HM6.7 (T3)	129 / 173	15000 / 33070	2.30 ~ 2.70 / 3.00 ~ 3.50
HL757-9A	CM QSB6.7 (T4I)	149 / 200	14700 / 32410	2.30 ~ 3.20 / 3.00 ~ 4.20
HL757TM-9A	CM QSB6.7 (T4I)	149 / 200	15200 / 33500	2.30 ~ 2.70 / 3.00 ~ 4.00
HL757-9S	HD HM6.7 (T2)	127 / 170	14000 / 30860	2.30 ~ 3.20 / 3.00 ~ 4.20
HL757-9SM	HD HM6.7 (T2)	129 / 173	13600 / 30000	2.30 ~ 3.20 / 3.00 ~ 4.20
HL955	CM QSB6.7 (T4F)	149 / 200	15100 / 33290	2.50 / 3.1
HL955 TM	CM QSB6.7 (T4F)	149 / 200	15600 / 34390	2.50 / 3.1
HL955A	CM B6.7 (S5)	149 / 200	15800 / 34380	2.80 / 3.70
HL955A TM	CM B6.7 (S5)	149 / 200	16500 / 36380	2.70 ~ 2.80 / 3.50 ~ 3.70
HL760-7	CM QSB5.9 (T2)	160 / 215	17900 / 39460	2.50 ~ 4.00 / 3.30 ~ 5.20
HL760-7A	CM QSB6.7 (T3)	160 / 215	17900 / 39460	2.50 ~ 4.00 / 3.30 ~ 5.20
HL760-9	HD HM6.7 (T3)	160 / 215	17900 / 39460	2.50 ~ 4.00 / 3.30 ~ 5.20
HL760-9A	CM QSB6.7 (T4I)	166 / 222	18350 / 40450	2.50 ~ 4.00 / 3.30 ~ 5.20
HL760-9A W/Handler	CM QSB6.7 (T4I)	166 / 222	19500 / 43000	3.30 / 4.32
HL760-9S	HD HM8.3 (T2)	153 / 205	17600 / 38800	2.50 ~ 4.00 / 3.30 ~ 5.20
HL960	CM QSB6.7 (T4F)	168 / 225	18800 / 41450	3.20 ~ 3.50 / 4.20 ~ 4.50
HL960 HD	CM QSB6.7 (T4F)	168 / 225	19300 / 42550	3.30 / 4.32
HL960A	CM B6.7 (S5)	168 / 225	19200 / 42330	3.20 ~ 3.30 / 4.20 ~ 4.32
HL965	CM QSL9 (T4F)	203 / 272	20100 / 44315	3.60 / 4.71
HL770-7	CM QSC8.3 (T2)	206 / 276	22800 / 50270	3.30 ~ 4.32 / 4.32 ~ 5.60
HL770-7A	CM QSL (T3)	209 / 280	23100 / 50930	3.30 ~ 4.32 / 4.32 ~ 5.60
HL770-9	HD HM8.9 (T3)	209 / 280	23100 / 50930	3.30 ~ 5.00 / 4.32 ~ 6.50
HL770-9A	CM QSL9 (T4I)	224 / 300	23500 / 51810	3.30 ~ 5.00 / 4.32 ~ 6.50
HL770-9S	HD HM8.9 (T2)	209 / 280	22500 / 49600	3.30 ~ 5.00 / 4.32 ~ 6.50
HL775-9S	CM QSM11 (T2)	227 / 304	24200 / 53285	3.8 ~ 4.7 / 4.8 ~ 6.1
HL970	SC DC09 (T4F)	232 / 311	23500 / 51810	3.70 ~ 5.20 / 4.80 ~ 6.80
HL970A	CM L9 (S5)	242 / 325	24200 / 53355	3.70 ~ 5.20 / 4.80 ~ 6.80
HL975	CM QSG12 (T4F)	246 / 330	26500 / 58430	4.80 / 6.30
HL975A CVT	CM X12 (S5)	250 / 335	26500 / 58430	4.20 ~ 5.20 / 5.50 ~ 6.80
HL780-7A	CM QSM11 (T3)	250 / 335	29300 / 64600	4.20 ~ 5.50 / 5.20 ~ 7.20
HL780-9	CM QSM11 (T3)	260 / 348	30000 / 66100	4.20 ~ 5.50 / 5.20 ~ 7.20
HL780-9A	CM QSM11.9 (T4I)	268 / 360	30300 / 66800	4.20 ~ 5.50 / 5.20 ~ 7.20
HL780-9S	CM QSM11 (T2)	260 / 348	29500 / 65040	4.20 ~ 5.50 / 5.20 ~ 7.20
HL780-9S UMA	CM QSM11 (T2)	260 / 348	32500 / 71650	5.40 / 7.10

※ Engine

CM : Cummins HD : Hyundai SC : Scania

Product line

Wheel loaders



Model	Engine	Horse power rated (kW/hp)	Operating weight (kg/lb)	Bucket capacity (SAE, m ³ /yd ³)
HL980	SC DC13 (T4I)	283 / 380	31000 / 68340	5.60 / 7.30
HL980A	CM X12 (S5)	265 / 355	30800 / 67905	5.00 ~ 6.30 / 6.50 ~ 8.20
SL730	YC YC6J125Z-T20	92 / 123	10200 / 22490	1.8 / 2.4
SL733	YC YC6J125Z-T20	92 / 123	10200 / 22490	1.8 / 2.4
SL733S	YC YC6J125Z-T20	92 / 123	10200 / 22490	1.7 / 2.2
SL735	YC YC6J125Z-T20	92 / 123	10200 / 22490	1.8 / 2.4
SL760	WP WD10G220E2	162 / 217	17100 / 37700	3.1 / 4.1
SL763	WP WD10G220E23	162 / 217	16800 / 37040	3.1 / 4.1
SL763S	WP WD10G220E23	162 / 217	16500 / 36380	3.0 / 3.9
SL765	WP WD10G220E23	162 / 217	16800 / 37040	3.1 / 4.1
SL765S	WP WD10G220E23	162 / 217	16500 / 36380	3.0 / 3.9

※ Engine

CM : Cummins WP : Weichai Power YC : Yuchai SC : Scania

Product line

Backhoe loaders



Model	Engine	Horse power rated (kW/hp)	Operating weight (kg/lb)	Capacity (SAE, m ³ /yd ³)	
				Loader	Backhoe
HB90	IC F4GE9454J*J	66 / 89	7830/ 17260	1.0 / 1.3	0.17 / 0.22
HB100	IC F4GE9484F*J	74 / 99	7900/ 17420	1.0 / 1.3	0.20 / 0.26
H930C	IC F4GE9454J*J	68.5 / 92	7830/ 17260	0.8 / 1.0	0.17 / 0.22
H940C	IC F4GE9484F*J	74.5 / 100	7900/ 17420	1.0 / 1.3	0.20 / 0.26
H930S	PK 1104C-44T	68.5 / 92	7830/ 17260	0.8 / 1.0	0.17 / 0.22
H930ST	PK 1104C-44T	70.1 / 94	8200/ 18080	1.1 / 1.44	0.17 / 0.22
H940S	PK 1104C-44T	74.5 / 100	7900/ 17420	1.0 / 1.3	0.20 / 0.26
H940ST	PK 1104C-44T	74.5 / 100	8250/ 18190	1.1 / 1.44	0.20 / 0.26
H940S-4WS	PK 1104C-44T	74.5 / 100	8900/ 19620	1.1 / 1.44	0.20 / 0.26

※ Engine

IC : Iveco PK : Perkins

Skid steer loaders



Model	Engine	Horse power rated (kW/hp)	Operating weight (kg/lb)	Capacity (SAE, m ³ /yd ³)
HSL650-7	KB V2230M	32.5 / 43.6	2625/ 5790	0.31 / 0.41
HSL650-7A	KB V2403M	35.5 / 47.6	2690/ 5930	0.31 / 0.41
HSL850-7	KB V3300	50.0 / 67.1	3290/ 7250	0.37 / 0.48
HSL850-7A	KB V3307	55.4 / 74.3	3290/ 7250	0.37 / 0.48
HSL810	YM 4TNE98	51.5 / 69.0	3260/ 7180	0.35 / 0.46

※ Engine

KB : Kubota YM : Yanmar

Product line

Road rollers



Model	Engine	Nominal output (kW/hp)	Operating weight (kg/lb)	Drum (mm/ft-in)	
				Width	Diameter
HR25T-9	DT D2011	22.5 / 33.6	2700/ 5952	1000(3' 3")	750(2' 6")
HR26T-9	DT D2011	22.5 / 33.6	2900/ 6393	1250(4' 1")	750(2' 6")
HR30T-9	DT D2011	22.5 / 33.6	3000/ 6614	1250(4' 1")	750(2' 6")
HR70C-9 W/SD	PK 1104C/D	61.5 / 84.0	7100/ 15653	1700(5' 7")	1250(4' 1")
HR70C-9 W/PFD	PK 1104C/D	61.5 / 84.0	7250/ 15984	1700(5' 7")	1140(3' 9")
HR110C-9 W/SD	DT TCD2012	96 / 130	11700/ 25794	2100(6' 11")	1500(4' 11")
HR110C-9 W/PFD	DT TCD2012	96 / 130	13100/ 28881	2100(6' 11")	1390(4' 7")
HR120C-9 W/SD	DT TCD2012	96 / 130	12300/ 27117	2100(6' 11")	1500(4' 11")
HR120C-9 W/PFD	DT TCD2012	96 / 130	13700/ 30203	2100(6' 11")	1390(4' 7")
HR140C-9 W/SD	DT TCD2012	103 / 140	12300/ 27117	2100(6' 11")	1500(4' 11")
HR140C-9 W/PFD	DT TCD2012	103 / 140	15400/ 33951	2100(6' 11")	1390(4' 7")
*HR120C-9 W/SD	DT BF4M 2012	95 / 129	12300/ 27117	2100(6' 11")	1500(4' 11")

※ W/SD : with smooth drum W/PFD : with pad foot drum * : Canopy

※ Engine

DT : Deutz PK : Perkins

Motor graders



Model	Engine	Horse power rated (kW)	Operating weight (kg)	Capacity (mm)	
				Max. Lift	Max. depth
HG130	CM 6BT5.9-C130	97	12000	410	560
HG170	CM 6BT5.9-C180	132	14500	450	535
HG190	CM 6BT5.9-C190	142	15600	450	535
HG220	CM 6BT5.9-C215	160	15800	450	535

※ Engine

CM : Cummins