





APPLICATIONS FOR CATERPILLAR®

MEGA ARTICULATED TRUCK TANK





Albuquerque, NM 87113

PARTS 🕗

EQUIPMENT **O**

700 Osuna Rd. NE



THERE'S WORK TO BE DONE

For over 45 years, Mega has been providing specialty haulage equipment for use in construction and mining operations. Our water haulage equipment, service bodies, bottom-dump trailers, equipment transports and other products are designed and manufactured to be reliable and durable machines. The knowledge and experience that comes from delivering over 6,000 machines is built into every product we make.

Our employees take pride in their workmanship and Mega has developed a reputation for manufacturing quality products that are built to last. Our sales and product support staff are known for providing solutions and demonstrating integrity throughout the ownership experience. Our product's value is reflected in our industry-leading brand recognition and resale value - Genuine Mega products have become the standard by which others are measured.

Mega products, parts and service can be found at OEM construction and mining equipment dealers around the world. Our sales and product support departments at Mega are available to help answer your questions. For more information, please contact us @ +1 505.345.2661 or toll free in the USA at 1.800.345.8889 or on the web at www.megacorpinc.com.

There's work to be done – and, from all of us at Mega, we want to help you do it!



Jim Kunz President Emeritus

⁶⁶ WE APPRECIATE YOU AND OUR PRODUCTS SHOW IT ⁹⁹



Follow us on social media.

#GENUINEMEGA www.megacorpinc.com





VALUE

- production tools
- ownership



- and requirements
- Materials and components used in the manufacture of Mega water tanks are chosen for high quality and durability rather than a low price point
- Mega water tanks feature the best interior baffling systems on the market resulting in a machine that is safe to operate with lower operating costs
- Key spray components are specifically engineered for severe duty heavy equipment service
- Mega spray system controls are designed to withstand the harsh corrosive environment of heavy construction and surface mining
- Mega water pumps are specifically designed for heavy equipment water tank service with features not found on standard off the shelf irrigation water pumps
- Mega spray heads (100% built in the USA) are the heaviest duty, most versatile, valve and spray fan nozzle on the market



- Our dealer relationships and a fully integrated machine provide seamless support and the highest level of machine availability
- Mega is the most recognized and valuable brand of tank on the market • Over 40 years of knowledge and experience with prime mover integration

- and advice to ensure seamless machine support
- Unsurpassed product warranties and dealer support

• The water tank is essential to the operation of production tools Mega water tanks provide the highest levels of dependability and longevity • The high quality Mega water tank provides a lower cost of ownership and more profit from

• Mega water tanks compliment the premier brands of prime movers • The superior longevity of Mega water tanks provides high resale value lowering the cost of

DESIGN AND MATERIALS

 Mega works closely with OEM manufacturers to ensure our tanks properly fit, load, and interface with the prime mover resulting in a fully integrated machine Mega tanks meet or exceed applicable ISO/SAE/DOT recommended practices

- Every Mega water tank includes a full set of Operation and Service Manuals
- www.megacorpinc.com provides useful information and complete contacts for support
- Phone, online and on-site support for dealers and end users with 24 hr/day parts

MAC/MAT- MEGA ARTICULATED TRUCK TANK



GENUINE MEGA DESIGN WITH IMPROVED PERFORMANCE & COST EFFECTIVENESS

Mega manufactures a complete line of water tanks for Caterpillar® articulated prime movers. Mega offers these products for dealer installation in kit form (MAC) or as a factory installation with Mega provided CAT® chassis (MAT). The MAC kit requires a dealer/customer supplied truck chassis. When purchased as a complete machine the machine is fully assembled and tested prior to shipment. Factory installation and testing are available on some models which may be shipped assembled from our factory in Albuquerque, N.M. depending on customer requirements and truck model. Purchasing your complete solution directly from Mega streamlines the ordering process and significantly reduces the complexities related to delivery timing and shipping.

Every tank includes a complete set of technical manuals detailing installation, operation, maintenance, inspection and replacement parts. Mega tanks are constructed with premium materials and are inspected throughout the manufacturing process to produce the best water tanks and spray systems available.

Mega stocks a complete line of service and repair parts, orders can be placed on-line through our website or by phone. Our Mega Product Support team is available to assist with all facets of installation on-site, by phone, or e-mail. Speak with your Mega sales representative for complete details.

Available Mega MAC/MAT Water Tanks for CATERPILLAR® Articulated Trucks

MEGA MODEL	NOMINAL CAPACITY	PRIME MOVER	CHASSIS CONFIGURATION
MAC5	19,000 liters/5,000 gallons	CAT 725	STANDARD or LONG WHEELBASE
MAC6	23,000 liters/6,000 gallons	CAT 730	STANDARD or LONG WHEELBASE
MAC6 FB*	23,000 liters/6,000 gallons	CAT 730	STANDARD or LONG WHEELBASE
MAC7	27,000 liters/7,000 gallons	CAT 735	STANDARD WHEELBASE
MAC8	30,000 liters/8,000 gallons	CAT 735	LONG WHEELBASE
MAC8	30,000 liters/8,000 gallons	CAT 740	STANDARD WHEELBASE
MAC8	30,000 liters/8,000 gallons	CAT 740GC	STANDARD WHEELBASE
MAC9	34,000 liters/9,000 gallons	CAT 740	LONG WHEELBASE
MAC9	34,000 liters/9,000 gallons	CAT 745	STANDARD WHEELBASE
MAC10	38,000 liters/10,000 gallons	CAT 745	LONG WHEELBASE

For other tractor models and custom sizes please contact Mega or your local dealer for more information. Sizes and models subject to change.

* FB-Flat Bottom

Our M.A.S.S. (Mega Anti Surge System) baffling provides the most stable, lowest profile, and longest-life tank on the market today. Chassis life is improved and maintenance decreased because our tanks are engineered in collaboration with Komatsu[®] to match their ROPS*, braking, and chassis load ratings. Mega tanks are designed with safety, performance, and durability in mind which ensures load stability, standard machine handling, and long chassis service life.

Mega tanks feature a proprietary baffling system that minimizes the effects of surging water while maximizing tank longevity. The tank mounting system utilizes line-bored rear pin mounts and flexible clamp front mounts that require no welding, making tank installation and removal simple. For more information on our rigid -frame water tanks please visit our website @ www.megacorpinc.com/equipment/water-articulated.asp

While Tanks May Look Similar On The Outside- It's What's Inside That Counts!

Fully welded baffling properly located ensures that your Mega tank is the strongest, most stable, longest lasting tank available today.

Multiple Tank Interior Access Ports _____ provides multiple points of access to internal tank compartments.

Rear Spray Bar With 3 Spray Head configuration where the center head acts as the primary sprayer while the two outboard swiveling heads act as supplemental spray.

Mega M3 Water Pump open centrifugal water pump capable of up to 800 gpm flow (up to 80 psi).

Rear Spray Bar With 4 Spray Heads hydraulically actuated and adjustable.

Mega M4 Water Pump open centrifugal water pump capable of up to 1,300 gpm flow (up to 120 psi).



STANDARD FEATURES

Standard features for Mega Articulated Truck Tank are subject to change and can vary by the type or model of tank. Availability of features may also vary by model. If you have any questions please contact your Mega sales representative at 505-345-2661 or toll free at 1-800-345-8889.

	CAT725 MAC	CAN TO MAC	CALLS MAC	CAT T35 MAC	CALL TAO MAC	CAT AS MAC	ATTA5 MAC
QUICK REFERENCE DIRECTORY	125 N	130 N	135 N	135 N	140 N	145 N	145 N
	NAC	NAC	AC	NAC	AC	AC	NAC
	5	6	7	8	8	9	10
Access Ladder With Hand Rails	\checkmark						
Anti-Surge Baffling System (M.A.S.S.)	\checkmark						
Camera Relocation Mounting Provision*	\checkmark						
Digital Spray Control System-DiSCS®			\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Direct Pin Mounting With Line-Bored Holes	\checkmark						
Electro-Hydraulic Spray Control System	\checkmark	\checkmark					
Exterior Paint	\checkmark						
External Water Lines	\checkmark	\checkmark					
Fill Port with Safety Grate & Anti-Skid Walkway 30 inch	\checkmark	\checkmark					
Fill Port with Safety Grate & Anti-Skid Walkway 36 inch			\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Flexible Front Mounting	\checkmark						
Hydraulic Oil Cooler	\checkmark	\checkmark				\checkmark	\checkmark
Internal Water Lines			\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
LED Lighting and Utility Lights	\checkmark						
M3 Series Water Pump	\checkmark	\checkmark					
M4 Series High Performance Water Pump			\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Mud Flaps	~	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
One Year Warranty	\checkmark						
Rear Spray Bar With 3 Spray Heads	\checkmark	\checkmark					
Rear Spray Bar With 4 Spray Heads			\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Technical Manuals	\checkmark						
Water Level Indicators	\checkmark						

MEGA DIGITAL SPRAY CONTROL SYSTEM FLEXIBLE, SMART, RUGGED

There is a growing demand for precise application of water spray for dust suppression in surface mining, and construction applications to promote water conservation and operator safety. To address these issues Mega has designed the DiSCS® - Digital Spray Control System.

DiSCS® utilizes CAN Bus* technology to operate the spray control system controlling the water pump, water spray, and water actuation. When combined with our GPS, DiSCS® provides a method to automatically regulate the amount of water spray applied relative to vehicle ground speed or distance traveled.



- Simple and rugged construction for heavy-duty operation • Adjustable switchpad brightness
- RAM[®] mount (where applicable) is fully adjustable to any operator • In-cab water level indicating system
- Total system pause function
- Work light and auxiliary controls
- Durable switchpad legend inserts

DISCS® SPRAY SYSTEM FEATURES AND BENEFITS



Distance-Based Spraying (Checkerboard) Alternating intermittent watering patterns reduces water consumption and ensures one steering tire and one drive tire remain on a dry surface.



F0)) Distance and speed-based operation modes utilize a GPS-based speed signal to automatically stop/start water flow when the vehicle stops/starts moving, while in GPS mode.

Speed-Based Spraying (Continuous Coverage)



speed.



Time Based Spraying (Banding)

Operator adjustable, full width, intermittent wet/dry pattern.



Manual Spraying

The system can be operated manually independent of GPS signal.



The DiSCS[®] compact switchpad is based on CAN Bus protocol and is water and dust resistant. The LED switchpad lights up with the many different watering patterns and controls.

Sequence-based intermittent spray system operation uses Pulse Width Modulation (PWM) to vary the amount of water flow while maintaining a continuous rate of water application, independent of



Reliability

DiSCS[®] utilizes Mega water pump, hydraulic motor, Mega spray heads, and electro-hydraulic controls. There are no complex modifications to the vehicle's hydraulic systems or powertrain.

DISCS® SPRAY SYSTEM FEATURES AND BENEFITS



Versatility

DISCS® is adaptable to most, if not all, pieces of water equipment found worldwide. DISCS® can be easily installed in the field on machines originally equipped with a Mega spray system, or can be retrofit to many older models equipped with a competitor's spray systems.

DiSCS[®] Retro-Fit Kits

Mega DiSCS® spray control can be applied to virtually any older Mega or competitor's water distribution equipment offering these advantages:

- Standardized operator and maintenance training.
- Genuine Mega Product Support and parts (also available on-line, and documentation).
- Readily available repair and maintenance components, common to most Mega water distribution products.

STANDARD DISCS® SUPERBOX FEATURES

The DiSCS[®] Superbox is a water-tight, sealed compartment with weather-proof rating built for rugged use in the harshest environments for mining and construction.



Photo includes optional equipment, sold separately.

- The Superbox consolidates the hydraulic system solenoid logic controls in a weather-proof, easy-to-access enclosure that securely protects critical components.
- Externally-mounted system filter assembly to protect hydraulic control valves.
- Logic control modules include individual fusing and self-diagnostics to assist in troubleshooting.
- Durable wiring harness with Deutsch® connections throughout. Harness includes additional pre-wired functions for easy plug-and-play of additional functions.

WATER PUMP PROTECTION FEATURES FOR DISCS®

Soft Start/Stop

System controlled soft starts/stops to protect against operator induced sudden starts and stops that can decrease drive motor and water pump service life.

\checkmark Low water

Automatic soft-stop when low water level is detected which prevents the dry running of the water pump.

Overheating

Automatic soft-stop after extended water pump operation with spray heads and water cannon valves closed (no water flowing from the pump).

GPS SYSTEM FOR DISCS®

The DiSCS® Global Positioning System (GPS) works with existing DiSCS® 2.0 Mega spray system hardware which includes water pump, hydraulic motor, spray heads, and DiSCS[®] 2.0 electro-hydraulic controls. A self-contained GPS unit is used to determine ground speed.



GPS-Based Sensing

DISCS® uses GPS data to determine ground speed, the GPS system is universal, there is no special application-specific engineering required and the system is not vulnerable to interference like radar-based systems.

Self-Contained

DiSCS® does not require connections to other vehicle systems to determine speed. Easily adaptable to a wide variety of machine applications.

The DiSCS® system utilizes a pulsing strategy, to automatically limit the amount of water consumed, based on vehicle speed while maintaining road dust control coverage. Utilizing the pulsing strategy avoids the addition of complex and costly variable flow hydraulic systems and the resulting impact on machine reliability. Multiple application choices are available-continuous water layer, checker boarding and operator selectable.



Automatic Shut-off

move again.





 \checkmark

Automatic Water Consumption Reduction

In GPS mode the system automatically shuts off the flow of water as the vehicle comes to a stop to prevent puddling. Spraying automatically resumes as the machine begins to

MEGA ELECTRO-HYDRAULIC CAB CONTROL

The in-cab spray control module provides independent control of each spray head, water valve, and optional accessories. Included in the cab control module is an LED water level indicator. Our control module is built for rugged use in the harshest environments of mining and construction.

Electro-Hydraulic Spray Control System

For the most demanding mining and construction environments we provide the Mega electro-hydraulic spray control system. The cab control module operates our Mega proprietary hydraulic solenoid spray control module that individually actuates all spray head valves and water valves. The spray control system operates independently from the water pump drive circuit. The solenoid module is housed in a weather tight steel housing. Mega fully supports these systems with spare parts and full time Product Support.



MEGA Cab Control



Water Level Indicators

There are two electronic water level indicators, one in the cab control module inside the cab and the other on the solenoid control module mounted on the tank for easy viewing while filling.

MEGA WATER PUMPS

The heart of the Mega spray system is the water pump. The water pump is powered by the vehicle's hydraulic system. Mega spray controls ensure proper integration with the chassis' hydraulic system and ECM.

The Mega M3 series heavy-duty water pump features a direct bolt-on hydraulic motor mount and steel splined coupling to simplify drive motor connection. Heavy-duty shaft and dual bearing design provide long life and high water output for superior spray pattern and water cannon performance.

The Mega M4 series high performance water pump also features direct bolt-on hydraulic motor mount and steel splined coupling to simplify drive motor connection. The vented frame cavity prevents damage from over-greasing and allows the use of an auto lubrication system. The M4 pumps are available in both standard cast iron as well as corrosion-resistant models with stainless steel waterways and fully stainless steel.



MEGA M3 Series



MEGA M4 Series



MEGA M4 Series Complete Stainless Steel



MEGA SPRAY HEAD VALVES



The Mega hydraulic spray head valve utilizes a custom-made, high quality, heavy-duty, double-acting hydraulic cylinder to open and close the valve portion of the spray head. This spray head is suitable for any heavy equipment prime mover, and requires a hydraulic spray control system.

HAVE CORROSIVE WATER? WE OFFER COMPLETE STAINLESS STEEL SPRAY HEADS

Our complete stainless steel spray heads are best suited to resist corrosion and abrasion by the harsh waters often found in mining and construction environments. Stainless steel's resistance to corrosion and durability along with low maintenance make Mega stainless steel spray heads the ideal spray head for the toughest environments. This is an optional feature.

Mega Spray Heads Valves are FULLY Adjustable!

Mega spray heads are adjustable and can be fine tuned to provide the optimal water distribution for a specific application. This allows for high efficiency, reduced water consumption, and prevention of roadway over watering.






Mega Hydraulic Spray Heads






Spray Capability


Mega spray head valves are fully adjustable for fan width, fan volume, and fan direction. When combined with swivels (see optional features) on the spray bar, fan direction can be adjusted on two axis. Mega spray heads provide a consistent flat fan spray over a very wide area. One or two spray heads are capable of suppressing dust on a road up to 27 meters (90 feet) wide.




Spray Head Configuration Flow Rates-Mega M3 Water Pump



Total flow rates of different spray head configurations. The approximate total flow rates in gallons/minute (left vertical axis) and liters/minute (right vertical axis) of three possible spray head configurations. The "fine spray" opening is 1/4 inch in height, and the "heavy spray opening" setting is 3/8 inch in height.





Total flow rates of different spray head configurations. The approximate total flow rates in gallons/minute (left vertical axis) and liters/minute (right vertical axis) of four possible spray head configurations. The "fine spray" opening is 1/4 inch in height, and the "heavy spray opening" setting is 3/8 inch in height.

9

G STANDARD Features


MAC/MAT 7, 8, 9 and 10

STANDARD Features **D**



ACCESS LADDER WITH HAND RAILS

Mega tanks include an access ladder to the top of the tank. Our standard ladder features tread grip rungs for a sure-footed grip and hand rails at the top of the ladder allowing safe access to the top of the tank. Optional customized safety railing is available upon request to meet your exact requirements.



ACCESS PORTS

Access ports provide additional access to the interior of the tank beyond the standard access provided through the fill port. This provides multiple points of access to internal tank compartments and includes internal ladder rungs on both sides of tank. Availability varies by model.



ACCESS MANWAYS

Larger Mega tanks include access manways through the main transverse baffles of the tank.




CAMERA RELOCATION MOUNTING PROVISION

A camera mounting bracket to relocate the camera from the truck to the water tank.




DIRECT PIN MOUNTING WITH LINE-BORED HOLES

Mega tanks pin directly to the rear pivot mounts of the truck chassis. Line boring the rear pivot mounts ensures accurate direct pin installation of the tank. Mega tanks do not require welding to the frame. New pivot pins and shims are supplied with the tank.



EXTERIOR PAINT

Mega tanks are abrasive blasted prior to application of anti-corrosive primer. The exterior top coat is color matched to the current manufacturers color. *Custom graphics are* available upon request.



EXTERNAL WATER LINES

External waterways feeding front spray, vertical side spray, and water cannon are external to the tank. Available on MAC 5 and 6 only.



FILL PORT WITH SAFETY GRATE AND ANTI-SKID WALKWAY

The standard fill port includes a bolt-in safety grate. For safer access to the fill port, an antiskid walkway is provided. The walkway extends from the access ladder on the front bulkhead to the fill port.






The truck chassis is allowed to flex beneath the spring type front mounting tie downs. No welding is required to install these mounts.




pump operation.



MUD FLAPS

All clearance, stop, and tail lights on Mega tanks are LED for long life and low maintenance. Two work lights are mounted on the rear bulkhead of the tank beneath water shedders. The lights are controlled by switches on the cab control.



ONE-YEAR WARRANTY

Mega protects your investment by providing a one-year warranty against defects in materials and workmanship. Extended warranties are available for purchase.

REAR SPRAY BAR WITH SPRAY HEAD VALVES

The rear spray bar is designed to fully utilize the capability of the water pump. The standard rear spray bar is constructed of carbon steel pipe. Optional stainless steel spray bars and spray heads are available as well as swivel couplings. See our optional features.

TECHNICAL MANUALS

available for purchase.







G STANDARD Features

HYDRAULIC OIL COOLER

The hydraulic oil cooler helps prevent overheating during extended water

INTERNAL WATER LINES

Internal waterways feeding front spray, vertical side spray, and water cannon are external to the tank. Available on MAC 7, 8, 9 and 10 only.

LED LIGHTING AND UTILITY LIGHTS


Mud flaps fore and aft of rear drive tires are standard equipment on all Mega tanks.

Mega water tanks include a complete set of technical manuals detailing installation, operation, maintenance, inspection and replacement parts. Additional manuals are

OPTIONAL FEATURES

Optional features for Mega Articulated Truck Tanks are subject to change and can vary by the type or model of tank. Availability of features may also vary by model. If you have any questions please contact your Mega sales representative at 505-345-2661 or toll free at 1-800-345-8889.

	CALLE	CAN YOU MAC	CALIS	CALLOT MAC	CALITY	CAN MAC	CAT 745	ATTA5 MAC
QUICK REFERENCE DIRECTORY		MAC	MAC	MAC	MAC	MAC	MAC	MAC
		5	6	7	8	8	9	10
Additional Technical Manuals		\checkmark	\checkmark	\checkmark	\checkmark	 ✓ 	\sim	\checkmark
Adjustable Stream Nozzles (Fan or Fog)		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Anti-Siphon Fill Pipe		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Camera Relocation Cable		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Conical Fill				\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Corrosion Resistant Package				\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Digital Spray Control System-DiSCS®*		\checkmark	\checkmark					
Drain Valve		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\sim	\checkmark
Dump Bar		\checkmark	\checkmark	\checkmark	\sim	\checkmark	\sim	\checkmark
Factory Installation		\checkmark	\checkmark	\checkmark	\sim	\checkmark	\sim	\checkmark
Fall Protection Tie-off Points		\checkmark	\checkmark	\checkmark	\sim	\checkmark	\sim	\checkmark
Foam Agent System (Requires Water Cannon)		\checkmark	\checkmark	\checkmark	\sim	\checkmark	\sim	\checkmark
Front Bumper Spray (Special Request)		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\sim	\checkmark
Hose Reel		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\sim	\checkmark
Interior Coatings (Epoxy or Urethane)		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\sim	\checkmark
Magnesium Anodes		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\sim	\checkmark
On-site Assistance		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\sim	\checkmark
Quick Change Components Package (QCCP)		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\sim	\checkmark
Stainless Steel Spray Heads		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\sim	\checkmark
Self Loading		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Swivel Couplings on Rear Spray Bar				\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Vertical Side Spray		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Water Cannon		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark



FACTORY INSTALLATION

Mega offers complete factory installation for articulated truck tanks for both customer-supplied and Mega-provided tractors. Factory installation includes complete testing prior to delivery.



ADDITIONAL TECHNICAL MANUALS

replacement parts.

ANTI-SIPHON FILL PIPE

The anti-siphon fill pipe is used with any pressurized water source. It is specifically designed to accommodate municipal water systems and fire hydrants requiring an air gap to prevent water siphoning back into the supply.

CAMERA RELOCATION CABLE

An extension cable to relocate your camera from the truck to the water tank.

* Please go to our standard section for DiSCS[®] information.



Additional sets of manuals are available for purchase. Mega water tanks include a complete set of technical manuals detailing installation, operation, maintenance, inspection and



MEGA WATER CANNONS

Mega's water cannons are designed and built to perform in the most severe environments of mining and construction. Capable of water pressures and flows required for the mobile water equipment industry, Mega's water cannons are ideal for fire suppression, high pressure equipment washing, and most applications that require long-distance, and/or concentrated spray.

Specialty Nozzles

Mega's hydraulic water cannons can be fitted with a variety of adjustable nozzles to customize the spray pattern and distance. In addition to the standard straight bore nozzle, Mega offers fan to stream, fog to stream with foam eduction, and fog to stream nozzles. For more nozzle options please visit our website or ask your Mega sales representative for more information.

Adjustable Stream Nozzles (Fan or Fog)

Remote control hydraulic fan or fog stream nozzles allow adjustable stream patterns for use with Mega water cannons. This option requires the purchase of the Mega Water Cannon.





Foam Agent System

The foam agent system is compatible with any class of foam that can be nozzle-aspired. This system can be used for fires suppression or other air-aspirated foam applications. The system consists of a stainless steel (316 grade) foam concentrate tank, water cannon, and foam eduction nozzle. Our medium-expansion nozzles allow for adjustable foam percentages of 1%, 3%, 6%, and 10%, and possible flow rates of 350, 500, and 750 GPM.




The Mega foam tank is mounted externally on the water tank and is available in the following gallon sizes: 60, 120 and 200. Mega's foam agent system can be ordered as an option on a new Mega water tank or be purchased as a retro-kit installed to on an existing water tank.



60 gallon External Foam Tank







200 gallon External Foam Tank

HOW MEGA CAN HELP YOU OPTIMIZE YOUR WATER APPLICATIONS



Over-watering of haul roads has been the subject of increased study by mine planning and safety personnel. Many mines have improved their efficiency, lowered resource and equipment maintenance costs, and improved the safety of their working conditions by employing water conservation practices.



> SAFETY

Excessive watering of roadways decreases effective tire traction, increases braking distances, destabilizes fill slopes, and accelerates erosion. This places haulage truck operators at a higher risk of accidents.



> WATER WASTE

Water conservation is extremely important, particularly in drier climates where water is already a scarce and precious resource. Many governments have implemented strict regulations concerning water usage, and require mines to develop and adhere to a water conservation plan.

> LABOR AND RESOURCES Over-watered, eroding haul roads must be serviced and repaired more frequently. When using too much water, trucks are required to return to water fill stations more often. This wastes both fuel and man-hours as well as subjecting the over-watered roads to heavier traffic.

> TIRE WEAR

Well-maintained haul roads will have a compacted top layer of fine-cushioning particles protecting tires from the larger coarse, sharp rocks below. Over-watering erodes this protective top layer, subjecting tires to severe wear by the exposed coarse rocks. This is costly in terms of tire replacement, lower production rates and higher labor hours.




We understand that our most precious natural resources are limited. Water conservation is essential for reducing waste and for safe road conditions, which is why we emphasize efficient water usage methods and equipment.



CONICAL FILL

The Conical Fill allows for easier positioning of the water fill source over the main fill port of the tank.



Drain Valve

The quick dump option is a large drain located at the bottom rear of the tank. This option is available either manually or hydraulic remote actuated for MAC6 as 101 mm/4 inch diameter and for MAC 7 and MAC8 as a 203 mm/8 inch diameter.



DUMP BAR

Mega offers two hydraulically-actuated dump bars. Mega's pressurized dump bar sprays penetrating jets of water directly onto the ground. The gravity dump bar is fed directly from the bottom of the water tank and may be used with the water pump turned off to reduce water flow and pressure.



FALL PROTECTION TIE-OFF POINTS

Multiple fall protection, D-ring style tie-off points are welded to the top of tank.



FRONT BUMPER SPRAY KIT

The front bumper spray is commonly used to "sweep" a surface with high pressure fans of water. Spray heads are mounted to spray from both sides of the tractor. The spray heads are fully adjustable for vertical and horizontal directions. The location of the spray bar allows the truck hood to fully tilt and open for engine service. Front bumper spray may restrict cab access. This item is available by special request.



HOSE REEL

Hose reels installed on Mega tanks include a high quality water hose and an adjustable fog to stream nozzle. Hose reels come in various sizes and are available with manual, spring, or hydraulic rewind. Sizes vary by model.



MAGNESIUM ANODES

Magnesium anodes are placed in each tank compartment to reduce corrosion of the tank interior.

ON-SITE ASSISTANCE

The Mega Product Support team offers on-site technical assistance, service advice and training to facilitate implementation and help reduce field assembly and component repair time.

SWIVEL COUPLINGS ON REAR SPRAY BAR

Optional swivel couplings allow for vertical spray direction adjustment. Each spray head rotates horizontally to adjust water spray fan direction.

VERTICAL SIDE SPRAY

Two spray head valves are mounted on the front quadrant of the tank for spraying vertical fans of water.


QCCP-QUICK CHANGE COMPONENT PACKAGE

Quick change component packages provide specific operation-critical parts for the Mega water tank spray system. Stocking critical parts reduces downtime by eliminating delays related to acquiring replacement parts. QCCP kits are designed specifically for each tank configuration. Contact your Mega dealer for complete parts kit list details or contact your Mega sales representative at 1-800-345-8889 for more information.





BUY PARTS ONLINE www.megacorpinc.com












PARTS AND PRODUCT SUPPORT AVAILABLE 24 HOURS A DAY, SEVEN DAYS A WEEK. Product Support 505.345.2661 • U.S. 1.800.345.8889 • After Hours & Weekend 505.345.6988

SELF-LOADING CAPABILITY


MAC/MAT 5 and 6

Mega MAC/MAT water tanks feature optional self-loading ability via the discharge pump. Unique to Mega is the built in priming reservoir inside the water tank that floods the suction line with water when the valving is switched to load the tank. An auxiliary manual priming pump is also included. Optional suction hoses can be ordered separately.



MAC/MAT 7, 8 and 9

Mega's larger MAC/MAT water tanks also feature an optional self-loading capability via a separate pump station. The additional water pump is powered hydraulically by diverting hydraulic power from the discharge water pump via a manual diversion valve. The option includes two suction hoses, foot valve, and hose storage tubes.





SOLUTIONS FOR CORROSIVE ENVIRONMENTS

The Corrosion Resistant package protects against tank and component corrosion caused by the harsh waters often found in mining, construction and landfill environments. Protecting your tank against corrosion adds longevity and dependability to your tank and spray system. Corrosion resistant package not available on MAC 5 and 6 models.

The package consists of:

- Stainless steel spray bar
- Stainless steel spray head valves
- Corrosion resistant Mega M4 water pump with stainless steel waterways
- Stainless steel internal piping



STAINLESS STEEL SPRAY HEAD

The Mega stainless steel hydraulic spray head valve is engineered for use in the most severe environments. The stainless steel hydraulic spray head valve is interchangeable with the Mega aluminum hydraulic spray head valve. Mega hydraulic spray head valves are actuated by a stainless steel, double-acting hydraulic cylinder.

CORROSION RESISTANT MEGA WATER PUMP

The Mega M4 series corrosion resistant water pump features a centrifugal pump manufactured with a stainless steel volute case, packing mount, and impeller. All surfaces that are in continuous contact with water utilize stainless steel construction.





The Mega M4 series complete stainless steel water pump features a centrifugal pump manufactured with a stainless steel frame, volute case, shaft, and impeller. It is designed for maximum life in corrosive applications.

INTERIOR COATINGS (EPOXY AND URETHANE)

Mega tanks are abrasive blasted prior to the application of the interior coating. The epoxy lining is well suited for harsh, acidic, alkaline, and salty waters. Urethane lining is very effective in normal to salty waters. Coating data sheet and MSDS available upon request.

Stainless steel solenoid control module enclosure mounted on front bulkhead of tank

COMPLETE STAINLESS STEEL MEGA WATER PUMP

SHIPPING DIMENSIONS


All weights and dimensions are subject to change. Tank weights and specs are given without water in the tank. Tank specifications are available for earlier models-please contact Mega Sales for more information.

MEGA MODEL & PRIME MOVER	CHASSIS CONFIGURATION	NOMINAL CAPACITY	OVERALL LENGTH	overall Height B	overall width C	TANK WEIGHT
	SWB-Standard Wheel Base	19,000 liters	10,287 mm	4039 mm	2,845 mm	22,984 kg
MAC5 CAT725		5,000 gallons	405 in	159 in	112 in	50,670 lbs
MAC5 CAT725	LWB-Long Wheel Base	19,000 liters	11,871mm	3,957 mm	2,804 mm	24,630 kg
MAC5 CAT725		5,000 gallons	467 in	156 in	110 in	54,300 lbs
MAC6 CAT730	SWB-Standard Wheel Base	23,000 liters	10,922 mm	4,496 mm	2,845 mm	24,925 kg
MACO CAT 730		6,000 gallons	430 in	177 in	112 in	54,950 lbs
MAC6 CAT730	LWB-Long Wheel Base	23,000 liters	11,887 mm	4,191 mm	2,845 mm	26,463 kg
		6,000 gallons	468 in	165 in	112 in	58,342 3 lbs
MAC6 CAT730 FB	SWB-Standard Wheel Base Flat Bottom	23,000 liters	10,871 mm	4,470 mm	2,946 in	27,397 kg
		6,000 gallons	428 in	176 in	116 in	60,400 lbs
MAC6 CAT730 FB	LWB-Long Wheel Base Flat Bottom	23,000 liters	10.80 mm	4,115	2,946 in	26,761 kg
		6,000 gallons	425 in	162 in	116 in	59,000 lbs
MAC7 CAT735	SWB-Standard Wheel Base	27,000 liters	11,657 mm	4,394 mm	3,353 mm	35,153 kg
		7,000 gallons	459 in	173 in	132 in	77,500 lbs
MAC8 CAT735	LWB-Long Wheel Base	30,000 liters	12,929 mm	4,140 mm	3,429 mm	37,458 kg
		8,000 gallons	509 in	163 in	135 in	82,581 lbs
MAC8 CAT740	SWB-Standard Wheel Base	30,000 liters	11,709 mm	4,674 mm	3,429 mm	37,376 kg
		8,000 gallons	461 in	184 in	135 in	82,400 lbs
MAC9 CAT745	SWB-Standard Wheel Base	34,000 liters	12,268 mm	4,757 mm	3,429 mm	38,601 kg
		9,000 gallons	483 in	187 in	135 in	85,100 lbs


TANK ONLY SHIPPING DIMENSIONS

All weights and dimensions are subject to change. Tank weights and specs are given without water in the tank. Tank specifications are available for earlier models-please contact Mega Sales for more information.

MEGA MODEL & PRIME MOVER	CHASSIS CONFIGURATION	NOMINAL CAPACITY	overall Length	overall Height B	overall width C	TANK WEIGHT
	SWB-Standard Wheel Base	19,000 liters	5,613 mm	2,540 mm	2,894 mm	4,513 kg
MAC5 CAT725		5,000 gallons	221 in	100 in	114 in	9,950 lbs
MAC5 CAT725	LWB-Long Wheel Base	19,000 liters	7,010 mm	1,930 mm	2,804 mm	5,579 kg
MACS CAT 725		5,000 gallons	276 in	76 in	111 in	12,300 lbs
	SWB-Standard Wheel Base	23,000 liters	5,588 mm	2,718 mm	2,896 mm	4,831 kg
MAC6 CAT730		6,000 gallons	220 in	107 in	114 in	10,650 lbs
	LWB-Long Wheel Base	23,000 liters	7,087 mm	2,201 mm	2,896 mm	6,123 kg
MAC6 CAT730		6,000 gallons	279 in	89 in	114 in	13,500 lbs
MAC6 CAT730 FB	SWB-Standard Wheel Base Flat Bottom	23,000 liters	6,934 mm	2,388 mm	2,870	6,123 kg
		6,000 gallons	273 in	94 in	113 in	13,500 lbs
MAC6 CAT730 FB	LWB-Long Wheel Base Flat Bottom	23,000 liters	6,934 mm	2,388 mm	2,870 mm	6,123 kg
		6,000 gallons	273 in	94 in	113 in	13,500 lbs
MAC7 CAT735	SWB-Standard Wheel Base	27,000 liters	6,858 mm	2,870 mm	3,353 mm	8,165 kg
		7,000 gallons	270 in	113 in	132 in	18,000 lbs
MAC8 CAT735	LWB-Long Wheel Base	30,000 liters	7,950 mm	2,413 mm	3,429 mm	8,845 kg
		8,000 gallons	313 in	95 in	135 in	19,500 lbs
MAC8 CAT740	SWB-Standard Wheel Base	30,000 liters	6,883 mm	3,124 mm	3,353 mm	8,618 kg
		8,000 gallons	271 in	123 in	132 in	19,000 lbs
		34,000 liters	7,192 mm	3,209 mm	3,353 mm	10,433 kg
MAC9 CAT745	SWB-Standard Wheel Base	9,000 gallons	283 in	126 in	132 in	23,000 lbs



Drawings do not represent all tank models. Optional features vary.



Drawings do not represent all tank models. Optional features vary.



Meet your **MEGA** team!

EQUIPMENT SALES >





JOHN STUBBS Regional Sales Manager jstubbs@megacorpinc.com 505.259.5975



Regional Sales Manager

kknotts@megacorpinc.com

505.322.9770



CLAUDIO CÓRDOVA M. Independent Sales Rep. Latin America ccordova@megacorpinc.cl 011.56996476128

JESSICA M. MANZANARES MEAGHAN SMITH Regional Sales Manager Sales Support Coordinator imanzanares@megacorpinc.com msmith@megacorpinc.com 505.341.6979 505.341.6993

PARTS SALES & PRODUCT SUPPORT $\mathbf{\Sigma}$



IZAYAH BRITO Parts Sales Representative ibrito@megacorpinc.com 505.998.6502



JEFF GUY Product Support Sales Representative jguy@megacorpinc.com 505.341.6989

We reach out **GLOBALLY** to take care of **YOU**

Wherever you are in the world, we're here to ensure you get the highest guality, most effective, and durable specialty haulage products in the industry. Mega is responsible for the design, development, manufacturing, marketing, and sale of products used in surface mining and construction projects worldwide.

Mega's products include all varieties of water haulage equipment, elevating scrapers, coal haulers, bottom-dump trailers, equipment transports, specialty dumper bodies, mobile pumps, stand tanks, parts, service and technical support. Mega's products are manufactured at its headquarters in Albuquerque, New Mexico, U.S.A. as well as by its partners in Chile, Colombia, India, South Africa, India and Australia.

Parts and Product Support available 24 hours a day, Seven Days a week.



PRODUCT SUPPORT AFTER HOURS & WEEKEND

Saturday-Sunday 505.341.6988 Direct





OFFICE HOURS

Monday-Friday 7am-5pm 505.345.2661 Office 800.345.8889 U.S. Toll Free



AFTER HOURS & WEEKEND

Saturday-Sunday 505.918.7271 Direct

SCAN TO VISIT OUR PRODUCT SUPPORT WEB PAGE



BILL TAYLOR Product Support Sales Representative btaylor@megacorpinc.com 505.341.6988





DYLAN F. THOMAS Director of Sales & Marketing dthomas@megacorpinc.com 505.850.9800



JIM KUNZ Chief Development Officer/ Engineering Manager jkunz@megacorpinc.com 505.345.2661





BETZAIDA RUIZ Senior Graphic Designer bruiz@megacorpinc.com 505.341.6966



JOSE BARRAZA Parts Sales Representative jbarraza@megacorpinc.com 505.341.6969



KEVIN LEE Technical Writer klee@megacorpinc.com 505.341.6996



NORM REDENSHEK Director Process Control, Product Support & Parts Sales nredenshek@megacorpinc.com 505.235.4650

